

**NAUTIX****TECHNICAL DATA SHEET**

## **NON SKID COMPOUNDS**

*For one or two pack finishing paints*

Nautix **Non Skid compounds** is a special powder to be mixed in one or two pack paints. The selection of different size grid improve foot adhesion on deck..

Nautix **Non Skid Compounds** can be added to one or two pot finishing enamels or varnish.

### PROTECTION

Work in a well ventilated area.  
Wear suitable protective clothing, gloves, glasses and eye/face protection.

### PREPARATION

Estimated mixing ratio: 200 grams of non skid compounds for 0.75 litre of paint. This ratio can be adjusted compare to the non skid aspect targeted.  
Shake and stir thoroughly before use.

### APPLICATION

Shake and stir thoroughly during application.

### TECHN. DATA

Colour : colourless  
Pack sizes : 0,2 kg – 1 kg .  
Product weight Kg/L: 2 +/- 0,05. Volume solids : 100 % - COV : 0.  
Flash point: >100°C

### SAFETY INFO

Particular hazards associated with the preparation and safety recommendations:  
S 2 Keep out of the reach of children.  
Emergency phone number : +33 (0)1 45 42 59 59



Nautix – Z.I. des 5 chemins – 56520 Guidel – France

Tel: +33.(0)2.97.65.32.69

Fax: +33.(0)2.97.65.03.54

**info@nautix.com — www.nautix.com**



Before printing, think about environnement . août-10