



NAUTIX TECHNICAL DATA SHEET

DECK GRIP

One pack non skid paint

DECK GRIP is a one-pack non-skid deck paint (colourless, white, grey) providing a good feet adhesion on deck or companion way steps, etc.

Nautix **DECK GRIP** can be applied over polyester (GRP), epoxy (resin or paint), one- or two-pack enamels or varnishes and wood. This one pack paint is easy to apply. It's recommended to mix with thinner Nautix **DA** up to 10%.

The formulation of the product provides very high quality and hardness, good impact and abrasion resistance. This paint provides an outstanding resistance in the marine environment and is also resistant to washing with detergent.

PROTECTION

Work in a well ventilated area, wear suitable protective clothing, gloves and eye/face protection. Use in a well-ventilated area, otherwise use mask (EC Standard: AB). Wear imperatively protective goggles and PVC gloves.

PREPARATION

Wash with a detergent and degrease using a cloth soaked in Nautix **SD**.
Sand the surface (paper grade 400) that should be dulled. Rinse with fresh water and let dry.

APPLICATION

Stir thoroughly before use.
Do not apply under 10°C.

Application methods :

- Roller (specific foam roller + Nautix tray): Paint must be apply in one thin coat. Do not apply thick layer. Impregnate roller with paint and wring it well on the tray.
Apply the paint over a 50cm² surface sharply, stretching the paint to a maximum. Let it harden and if it is not enough apply one more coat when hand dry. (if you cross with 90 degrees, you will obtain better aspect)
- Spray gun : one or two coats and let it harden (nozzle : 2.0 to 2.2 mm- air pressure : 2 bars at the gun).
Thinner : NAUTIX **DA** - Maximum dilution 15 %.

DRYING TIME

TEMPERATURE	10°C	15°C	20°C	30°C
Hand dry / overcoating time	6 H	4 H	2 H	1 H
Dry	48 H	36 H	24 H	12 H

TECHN. DATA

Varnish : Alkyde, Solvent Naphta
Colour : Colourless, Grey, White. Finish : mate.
Pack sizes : 0,75 L
Coverage : 8 m²/Ltr for one coat - Product Weight Kg/Ltr : 1.55 +/- 0,05 - Volume solids: 55%.
COV : 391 gr/l - Viscosity : thixotropic - Flash point : 23°C<>55°C.

SAFETY INFO

Please carefully read labels before use. Particular hazards associated with the preparation and safety recommendations:
R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R 10 Flammable. S 2 Keep out of the reach of children. S 29 Do not empty into drains. S 46 If swallowed, seek medical advice immediately and show this container or label. S 61 Avoid release to the environment. Refer to special instructions/Safety data sheets. S 23 Do not breathe vapour S 24 Avoid contact with skin. S 51 Use only in well-ventilated areas. S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label. Marine Pollutant P. Emergency phone number : +33 (0)1 45 42 59 59



Nautix – Z.I. des 5 chemins – 56520 Guidel – France
Tel: +33.(0)2.97.65.32.69
Fax: +33.(0)2.97.65.03.54
info@nautix.com — www.nautix.com

